



AIRSTARTHOSSES

Air Start Hose Black Rubber Lavatory Service Dump Hose, 4-Inch is built to provide reliability on the tarmac. Our black rubber version provides resistant to UV and extreme condition. Translucent lavatory dump hoses can be convenient, but even UV-protected translucent hoses can degrade more quickly. For hot, sunny, or otherwise extreme environments, our heavy-duty 4-inch diameter black rubber lavatory dump hose is recommended. Anti crush. A/C to Lav cart hose Lightweight (1.5 lbs/feet).

BUILT TO EXCEED THE DEMANDING NEEDS OF THE GLOBAL AVIATION INDUSTRY

PROPERTIES : Tailor made solutions available.

Tailor made solutions available.

Temperature – 40°C to 90°C (-40°F to 194°F)

30% more resistance to abrasion than any other hose

A unique spiral protection protecting the polyurethane

Unrivalled lifespan. 4 times longer than any other hose used for the same application

Your reliable specialist for airstarthoses and coupling.

Printed copies are uncontrolled, and properties might change without any notification.

AVAILABLE LENGHTS : 8, 10, 12, 15 or 20 FEET or on request.

P/N ACP-BLACK LAV-8 Feet

P/N ACP-BLACK LAV-10 Feet

P/N ACP-BLACK LAV-12 Feet

P/N ACP-BLACK LAV-15 Feet

P/N ACP-BLACK LAV-20 Feet



Airstarthoses - Daviation BVBA
Industrialzone strohof
Kruisboommolenstraat 7/9
8800 Roeselare – BELGIUM

Tel +32.51.77.99.19
www.airstarthoses.com
info@airstarthoses.com

Self-Sealing Fill Coupling



Self-Sealing Lavatory Service Fill Coupling & Potable Water Fill Coupling built from Anodized aluminum to prevent bacteria. Prevent ramp spillage. Save time, coupling wear and fluid. The coupling can be disconnected from the aircraft without shutting off flow to the hose. Upon disconnection of the coupling, the integral poppet automatically closes preventing the pressurized line from discharging blue fluid onto the ramp formulated rubbers to ensure safe use and reliability on the tarmac. 3/4" potable water & 1 inch lav. service fill coupler with long-grip for easy aircraft hookup

Your reliable specialist for GSE hoses and couplings.

BUILT TO EXCEED THE DEMANDING NEEDS OF THE GLOBAL AVIATION INDUSTRY
CERTIFICATION : ISO CE

PROPERTIES :

- Anodized aluminium.
- Reversible.
- Stainless steel bearings
- Spare parts on stock.

Printed copies are uncontrolled, and properties might change without any notification.